Trac Backup

Error: Macro TracGuideToc(None) failed

```
'NoneType' object has no attribute 'find'
```

Since Trac uses a database backend, some extra care is required to safely create a backup of a <u>project environment</u>. Luckily, <u>trac-admin</u> has a command to make backups easier: hotcopy.

Note: Trac uses the hotcopy nomenclature to match that of <u>?Subversion</u>, to make it easier to remember when managing both Trac and Subversion servers.

Creating a Backup

To create a backup of a live <u>TracEnvironment</u>, simply run:

```
$ trac-admin /path/to/projenv hotcopy /path/to/backupdir
```

trac-admin will lock the database while copying.

The resulting backup directory is safe to handle using standard file-based backup tools like tar or dump/restore.

Restoring a Backup

Backups are simply a copied snapshot of the entire <u>project environment</u> directory, including the SQLite database.

To restore an environment from a backup, simply stop the process running Trac (i.e. the Web server or <u>tracd</u>), restore the directory structure from the backup and restart the service.

Note: Automatic backup of environments that don't use SQLite as database backend is not supported at this time. As a workaround, we recommend that you stop the server, copy the environment directory, and make a backup of the database using whatever mechanism is provided by the database system.

See also: TracAdmin, TracEnvironment, TracGuide

Trac Backup 1