

# The Trac Configuration File

## Error: Macro TracGuideToc(None) failed

```
'NoneType' object has no attribute 'find'
```

Trac configuration is done by editing the `trac.ini` config file, located in `<projectenv>/conf/trac.ini`.

## Global Configuration

Since version 0.9, Trac can also read the configuration from a global `trac.ini` file. These global options will then be merged with the environment-specific options, where local options override global options.

The global configuration is by default located in `$prefix/share/trac/conf/trac.ini`. It can be moved to a different location (for example, `/etc/trac.ini`), but that requires changing the file `trac/siteconfig.py` which gets created when Trac is installed.

## Reference

This is a brief reference of available configuration options.

### [trac]

database	<u>Database connection string</u> for this project
default_charset	Charset used in text files in the subversion repository (default is <code>iso-8859-15</code> )
default_handler	Name of the component that handles requests to the base URL (default is <code>WikiHandler</code> ) ( <i>since 0.9</i> )
repository_dir	Path to local Subversion repository
authz_file	Path to Subversion <u>?authorization (authz) file</u> .
authz_module_name	The module prefix used in the <code>authz_file</code> (See <code>FineGrainedPermissions?</code> )
check_auth_ip	Whether the IP address of the user should be checked for authentication ( <code>true</code> , <code>false</code> ) ( <i>since 0.9</i> )
ignore_auth_case	Whether case should be ignored for login names ( <code>true</code> , <code>false</code> ) ( <i>since 0.9</i> )
templates_dir	Path to the ClearSilver templates

### [project]

name	Project name
descr	Short project description
url	URL to the main project website
icon	URL to icon file to use as shortcut icon (favicon)
footer	Page footer text (right-aligned)

### [header\_logo]

src	URL to image to use as header logo
link	Destination URL to link to from header logo
alt	<i>alt</i> text for header logo

width Header logo width in pixels  
height Header logo height in pixels  
See also: [TracInterfaceCustomization](#).

## [logging]

log\_type Logging facility to use. (none, file, stderr, syslog, winlog)  
log\_file If *log\_type* is *file*, this should be a path to the log-file  
log\_level Level of verbosity in log (CRITICAL, ERROR, WARN, INFO, DEBUG)  
See also: [TracLogging](#)

## [attachment]

max\_size Maximum allowed file size for ticket and wiki attachments

## [notification]

smtp_enabled	Enable SMTP (email) notification (true, false)
smtp_server	SMTP server to use for email notifications
smtp_user	Username for SMTP server ( <i>since 0.9</i> )
smtp_password	Password for SMTP server ( <i>since 0.9</i> )
smtp_from	Sender address to use in notification emails
smtp_replyto	Reply-To address to use in notification emails
smtp_always_cc	Email address(es) to always send notifications to
always_notify_reporter	Always send notifications to any address in the <i>reporter</i> field
always_notify_owner	Always send notifications to the ticket owner ( <i>since 0.9</i> )

See also: [TracNotification](#)

## [mimeviewer]

enscript_path	Path to the Enscript program
php_path	Path to the PHP program
max_preview_size	Maximum file size for HTML preview ( <i>since 0.9</i> )
tab_width	Displayed tab width in file preview ( <i>since 0.9</i> )

## [ticket]

default_version	Default version for newly created tickets
default_severity	Default severity for newly created tickets
default_priority	Default priority for newly created tickets
default_milestone	Default milestone for newly created tickets
default_component	Default component for newly created tickets
restrict_owner	Make the owner field of tickets use a drop-down menu ( <i>since 0.9</i> )

## [ticket-custom]

Creates user-defined ticket fields.

## [timeline]

`default_daysback`      Default "depth" of the Timeline, in days (*since 0.9*)  
`changeset_show_files`   Number of files to show (-1 for unlimited, 0 to disable)  
`ticket_show_details`   Enable the display of all ticket changes in the timeline

## [browser]

`hide_properties`   List of subversion properties to hide from the repository browser (*since 0.9*)

## [wiki]

`ignore_missing_pages`   enable/disable highlighting CamelCase links to missing pages (*since 0.9*)

## [components]

(*since 0.9*)

This section is used to enable or disable components provided by plugins, as well as by Trac itself. The component to enable/disable is specified via the name of the option. Whether its enabled is determined by the option value; setting the value to `enabled` or `on` will enable the component, any other value (typically `disabled` or `off`) will disable the component.

The option name is either the fully qualified name of the components or the module/package prefix of the component. The former enables/disables a specific component, while the latter enables/disables any component in the specified package/module.

Consider the following configuration snippet:

```
[components]
trac.ticket.report.ReportModule = disabled
webadmin.* = enabled
```

The first option tells Trac to disable the report module. The second option instructs Trac to enable all components in the `webadmin` package. Note that the trailing wildcard is required for module/package matching.

See the *Plugins* page on *About Trac* to get the list of active components (requires `CONFIG_VIEW` permissions.)

See also: TracPlugins

*Note that prior to Trac r2335 (that applies to 0.9b1 and 0.9b2), you would use a [disabled\_components] section instead. See a ?previous version of this page for the details.*

---

See also: TracGuide, TracAdmin, TracEnvironment